



## *High Banks Speedway 2027*

### **LATE MODEL RULES**

#### **CAR/BODY:**

The Late Model Division is open to strictly American made cars manufactured after 1955.

Camaro/Firebird bodied cars up to 1992 are allowed.

Fiberglass bodies are allowed.

Plastic front fenders and rear quarter panels are allowed.

Any other make or model up to Current year permitted, exception: muscle car bodies (Camaro, Mustang, Charger) up to current year allowed. No 6<sup>th</sup> Gen bodies are allowed.

High down-force bodies and/or parts will not be permitted.

No ultra-light weight bodies will be permitted.

Carbon Fiber parts of any type are not allowed.

No mixing or matching body parts.

Body must remain stock appearing and mounted to the manufacturer's specification.

All forced air openings must be used for radiator or brake cooling only.

A metal firewall must separate the driver from the trunk area.

Front and rear stubs may be tied together.

Fenders and quarters may be trimmed at the wheel opening for tire clearance, a maximum 4 inches from tire, rolled with no sharp edges.

Fiberglass hood and fenders are permitted –No one piece front ends allowed.

Single side kick-off bars flush with the body are optional.

No external nerf bars of any type are allowed.

Lexan rub rails allowed between front and rear tires only, no sharp edges.

Reinforcement behind stock bumpers is permitted, if properly welded to the frame.

Bumpers must be at stock height.

No handmade nose pieces allowed.



## *High Banks Speedway 2027*

Altering the body and roof lines is not allowed.

No fabricated nerf bars are allowed on the front or rear bumpers.

Cars must have driver fire protection such as a stock original full firewall, minimum .040 steel fabricated firewall, or Super Late Model style footbox and interior.

Super Late Model style footbox must be totally enclosed and made of minimum .040 steel. Right side interior panel can taper upward to the right side of door bar.

All unnecessary holes in floor pan or firewalls must be covered with metal.

Floorboard must be made of .040 steel minimum.

Stock grills may be exchanged with steel or aluminum mesh.

No functional hood scoops or air cleaners that stick out of the hood are allowed.

Raised hoods are allowed.

All hoods must seal against the windshield.

Hoods and deck-lids must be properly fastened with quick release pins.

The maximum dimension for the vent window along the top of the door will be 12 inches and must go 90 degrees from the top of the door up to the A-post.

No interior spoilers, wings, skirting behind the rear tires or wind deflectors are allowed.

A rear spoiler, non-adjustable by driver, may be attached to the rear deck-lid, not to exceed 5 inches in height and 60 inches in length with a total maximum height off the ground of 41".

Must be 1/8 inch metal or 1/4 inch Lexan and control the flow of air over one surface only.

No rudders or forward mounting brackets allowed.

If a car is deemed to repeatedly contact the racing surface it will be black flagged with the corresponding finish. Front and rear windows are required.

Greenhouse body allowed. No lightweight Greenhouse components



## *High Banks Speedway 2027*

### **WINDSHIELD, GLASS, & MIRRORS:**

Front and rear windows are required.

Windshield must remain at factory angle with a minimum of three (3) bars, and placed such that objects would be reasonably deflected from entering the driver's compartment.

Rear view mirrors with a maximum width of 26 inches will be permitted.

Top of windshield is reserved for Series Sponsor and must be painted black. No points will be awarded without Sponsor decal.

### **FRAMES:**

Frame rails must be fabricated using a minimum of 2"x3", .083 or 2½"x 2", .083 steel tubing.

Rear clips may be fabricated. Fabricated rear clips must use a minimum of 2"x 2" steel tubing with .083" wall.

Non-approved frame or suspension modifications are subject to a minimum weight penalty of 200 lbs.

No hollow or titanium bolts allowed.

### **ROLL BARS:**

A steel roll cage consisting of continuous hoop not less than 1-3/4 inch outside diameter and must have a wall thickness of at least .095.

Cage must be mounted to frame in at least six places with proper bracing to protect the driver.

Four or more side bars are mandatory and must be as parallel with the ground as possible and located perpendicular to the driver, to provide maximum protection for the driver.

Steel door plate must be securely welded to outside of driver's side door bars and cover the area from the top door bar to bottom door bar from behind the driver including the footbox area with a minimum of 0.125 (1/8") magnetic steel plate.

Must utilize a full roll cage and be approved by High Banks Speedway officials.

### **ENGINE LOCATION:**

A crank shaft centerline height of 12" must be maintained. This will be checked with 5" blocks under the frame rails if needed.

All engines must be located so the center of the forward-most spark plug hole of the engine is 1 inch rearward of the center line of the upper ball joint.

All Engines must be centered in the frame, within a maximum of 1 inch offset for header clearance.



## *High Banks Speedway 2027*

### **EXHAUST:**

Mufflers are mandatory. 95 DBA OR LESS WILL BE STRICTLY ENFORCED!

Must extend under the car and behind the driver and be securely mounted.

Heat shields to cover exhaust system can be no more than 4 inches wide and no longer than the valve cover.

A minimum penalty for any car that is found to be too loud at any time by Track Officials will automatically start at the back of the A-Main regardless of qualifying position.

Crossover headers are allowed. No 180-degree, tri-y or merge collectors allowed when using this option.

Chassis style headers with either Tri-y or merge collectors are **not** allowed.

There will be a \$500 Header Claim rule in the Late Model Division.

### **IGNITION:**

Stock HEI ignition allowed but cannot be used with an external coil.

Coil must be similar in design to OEM.

No MSD boxes or similar type products.

Aftermarket or performance modules allowed.

Cell phones, smart watches, and / or Bluetooth devices will not be allowed in the racecar at any time during qualifying or race.

### **COOLING SYSTEM:**

Only one radiator mounted in front of the engine is permitted.

No electric water pumps.

Electric fans permitted.

Minimum 2-quart catch can and must be securely mounted.

Only V-belt pulleys are permitted.

Radiator Pan: 31" max width.



## *High Banks Speedway 2027*

### **TRANSMISSION:**

All cars must have stock OEM production passenger car 3 or 4 speed transmission with all working gears. No racing transmissions allowed.

T-10 transmissions will be allowed as long as they have OEM or OEM style/type gears with correct ratios and correct cut on gears- NO STRAIGHT CUT GEARS ALLOWED.

No automatic or racing transmissions allowed, unless pre-approved by High Banks Speedway Track Officials, due to extenuating circumstances.

No Transmission gear may be closer than 1.23:1 of the final drive ratio of 1:1.

### **CLUTCHES:**

Minimum 10-inch stock steel type clutch assembly only. Hydraulic throw-out bearings are allowed.

No turning or drilling of flywheels are allowed; aluminum or special type flywheels are not permitted.

No multiple disc clutches permitted.

The minimum weight of the clutch, flywheel, and bolts shall be 30 lbs.

Full disc. No aluminum components.

### **DRIVE SHAFTS:**

No aluminum or carbon fiber drive shafts, yolks, or slip yolks allowed.

Must have a minimum of two 2-inch-wide X ¼inch thick 360-degree brackets placed around the drive shaft fastened to floor or cross member preventing the shaft from being dislodged & dropping onto the racing surface. All brackets must be approved by High Banks Speedway officials.

### **REAR END:**

No cambered rear-ends allowed.

No aluminum center sections or components are allowed. Aluminum lowering blocks and drive plates are allowed.

Welded spider gears or steel spools may be used. No ratcheted or limited slip rear-ends allowed.

No gun-drilled or titanium axles allowed.

No titanium lower input shafts are allowed.



## *High Banks Speedway 2027*

No rear sway bars are allowed.

Final drive ratio must be between 5:20 to 6:20. Subject to change after testing.

No quick-Change rear ends will be permitted.

### **BRAKES:**

Working calipers or drums on all four wheels is required.

OEM brake parts only. No carbon fiber. No aluminum calipers. No aluminum or titanium components.

Calipers must be solidly mounted.

Rotors cannot be lightened or drilled and must not be less than .060 inches of minimum. (i.e., Minimum stamped on rotor is 1.2 inches, cannot be measured less than 1.14 inches).

No solid rotors allowed.

Racing type brake pedals and master cylinders permitted.

Brake bias adjusters or valves are permitted.

### **TREAD WIDTH:**

78 inches maximum, measured from the outermost part of the tire, at spindle height, zero tow in, front and rear. Must fit High Banks Speedway gauges as presented for inspection – No tolerance.

Must meet tread width of 78” pre-race and post-race as presented.

### **WHEELBASE:**

108” both sides +/- 1/2”.



## *High Banks Speedway 2027*

### **FRONT SUSPENSION:**

Only one shock per wheel.

A factory stock production front stub must be used. Fabricated Camaro stubs are also allowed and MUST run Camaro components. This must fit the approved High Banks Speedway jig. Any alteration of pickup points will disqualify cars from competition. Lower control arms must remain parallel to each other.

All stock suspension and steering mounting locations must be used and unaltered.

Stock production lower A-frames make to make are permitted. No modifications or alterations of lower A-frames, sway bar mounts, or lower shock mount. No spherical bearing, monoball, offset bushings or articulated bushings are allowed. Aftermarket steel bushings are allowed.

Front coil springs to be 9 ½" minimum height and must be mounted in the stock original position. Ball joint mounts may be altered to permit the use of a larger ball joint but may not relocate the ball joint.

No modifications or alterations of spindles except for reaming the ball joint hole. Must retain taper in spindles.

Only permitted spindle is GM #1 or GM#2.

Lower control arm must match the manufacturer of the stub.

After-market steel upper control arms are permitted. Aluminum cross shafts are permitted. Stock upper control arm mounts may be changed. Rebuildable ball joints are permitted.

After-market non-externally adjustable steel twin tube shocks are permitted. No aluminum shocks, mono tube shocks, external shock reservoirs, or shradar valves are permitted.

Steel weight adjusters are permitted.

Multi-piece sway bars are not allowed, only single piece construction / steel only.

No coil bind, bump stops, no bump stop springs or any device that will limit travel.

Aftermarket center link will be permitted (Howe Part #23396 or All-Star Part # AL56330).

Howe or Allstar adjustable idler arms will be allowed.



## *High Banks Speedway 2027*

### **REAR SUSPENSION:**

Only one shock per wheel.

Steel Panhard bar with steel or aluminum mounting brackets.

Only one solid steel upper link allowed. All mounting hardware must be made of steel and can be fabricated.

Steel trailing arms permitted. Location optional.

Three-link suspension.

Truck arms allowed with solid bushing only.

All heim joints must be made of steel.

Must use 5-inch diameter springs.

Rear weight-jackers are optional, if used they must be made of steel.

Spring and coil mounts must be made of steel and can be fabricated. Location optional.

No coil eliminators (sliders) allowed.

Leaf springs are allowed.

One spring rubber per wheel.

### **WHEELS & TIRES:**

Steel wheels only. Maximum width is 8 inches.

No wheel weights are allowed.

The mandatory track tire will be a Hoosier F70 series tire. All competitors are allowed to purchase up to 4 new tires (2 right side and 2 left side) and must run those four tires for BOTH qualifying and competition (Dash & Feature Races) for two consecutive nights of racing. The top 7 finishers will have their tires impounded after the final Feature Race of the evening.

No wheels or tires protruding outside of body panels.

Wheel Spacers are allowed, with minimum of 3 threads showing outside of lug nut.

No tire bleeders are allowed.



## High Banks Speedway 2027

### **STEERING:**

Steering Quickener is allowed.

### **WEIGHT** (*Note: Weight MUST be posted on Passenger A-Pillar!*)

Up to 365 Maximum C.I.D. Stock Stub 2,950lbs. – Fab Stub 3,000lbs. Minimum

Over 365 Minimum C.I.D. Stock Stub 3,150 lbs. – Fab Stub 3,200 lbs. Minimum (small blocks only)

Crate Engine Stock Stub 2,950 lbs. – Fab Stub 3,000 lbs. Minimum

The maximum left side weight shall be 57% of total weight.

### **FUEL**

RACING FUEL ONLY permitted and must be purchased from High Banks Speedway directly.

Racing fuel shall not be blended with any other gasoline or any additives, aniline, or its derivatives, nitro compounds, or other oxygen containing compounds.

It is the competitor's responsibility to ensure that fuels are not mixed by using previously used storage containers.

Icing or cooling of fuel system will not be permitted in the pit or racing areas.

Icing, Freon type chemicals, or refrigerants may not be used in or near the fuel system.

Pressure systems will not be permitted.

Any concealed pressure type containers, feed lines, or actuating mechanisms will not be permitted, even if inoperable.

All fuel must pass High Banks Speedway gravity test or may be subject to additional testing.



## *High Banks Speedway 2027*

### **FUEL TANK**

Stock gas tanks must be removed and replaced with a fuel cell with 22 gallons maximum.

Fuel cells must be enclosed in approved metal container. Containers must be securely mounted behind the driver in the trunk area and have all steel braided fuel lines or lines sealed in pipe or conduit, running under the floorboard.

Fuel systems must be well protected from rupture and must have a flapper or check valve in the vent hose.

Fuel cell height 9 inches minimum, measured from the bottom of the cell to the ground.

It is recommended that fuel cell be supported by three straps a minimum of 1-inch square tubing and secured by at least two straps length wise and two cross wise –all bolted to the frame.

A reinforcement plate of not less than 1/8-inch magnetic steel must be installed behind the fuel cell. Plate must be welded to cage and must extend the entire width and height of the fuel container.

Only one (1) gasoline filter may be used between the fuel cell and fuel pump. The location and size of the filter must be acceptable to High Banks Speedway Officials.

Oberg or SRI antisiphon valve is mandatory; mounted near fuel cell after fuel filter.

### **Notes:**

**OUT-OF-TOWN CARS:** High Banks Speedway invites all Out-of-Town competitors. Because of differing levels of competition, High Banks Speedway reserves the right to adjust gear, total or car weight bias on an individual basis.



## *High Banks Speedway 2027*

### **ENGINE REQUIREMENTS AND OPTIONS**

No external vacuum pumps or pan-vacuum systems allowed on either engine option.

#### **ENGINE OPTION 1: Crate Engine**

Engines must Unaltered GM # 88958604/88869604 with factory seals only and must remain in the “as shipped” condition. The Track Officials reserve the right to confiscate, impound, and/or replace any competitor’s engine at any time. Competitors’ refusing confiscation, impounding and/or replacement, will be disqualified from the event, and all future events until engine issue has been solved. Disqualification includes forfeiture of all monies, points and contingencies earned for that event. Teams may be subjected to additional fines, penalties and or point’s loss, based on inspection of the engine. Teams fined or penalized for engine infractions are not eligible for competition until all fines and/or penalties have been fulfilled or paid.

- No aftermarket engine dampers are permitted, oil coolers are recommended, use of or installation of an open or closed loop vacuum system, to evacuate air from the engine is a speed enhancing alteration and will subject the team(s) to all penalties as described in Engine Option 1 Sealed Component Violation, melanized (hardened) distributor gear must be used on distributor to prevent engine damage, requires an externally balanced flywheel.

#### **Approved Engine ONLY**

GM part number 88958604

#### **Carburetor of Engine Option 1 ONLY**

Holley 650 CFM 4150 HP carburetor, “box-stock”, is mandated, no exceptions. Carburetor must be securely fastened to the intake manifold with one (1) .0625-inch (1/16”) or smaller flange gasket. Spacers or drop-in spacers, alteration, physical changes, machining, re-shaping, or tampering with any part of the original parts, internal or external, is prohibited. Only Holley replacement parts are permitted for use and must match original parts:

Jets, bleeds, needle and seat, emulsion bleeds power valves, accelerator pump nozzles, accelerator pump cam, arm, and linkage must remain on carburetor, but can be adjusted so that the secondary accelerator pump does not work.

High Banks Speedway reserves the right to impound and/or confiscate any carburetor at any time during or after an event. Failure to comply with this will subject the team(s) to disqualification from the event and forfeiture of all monies and points earned for that specific event as well as subject the team to additional penalties and or probation. Failure to relinquish a confiscated carburetor or component(s) result in an indefinite suspension from competition until such time as illegal part has been received by High Banks Speedway track management as well as possible fines.



## *High Banks Speedway 2027*

### **ENGINE OPTION 2**

Minimum 311 C.I., American made V-8 steel or cast-iron engine, OEM stock. May be interchanged in family line of car only, i.e.: any Chevrolet may be installed in any other GM car, but not a Ford or Mopar. Engine must match Frame / Chassis being used, body make optional. 1" Motor setback shall be allowed. Engine must be located where #1 spark plug lines up with center line of upper ball joint. No lowering of engine is allowed. All engines must be assembled with stock OEM type parts only. The distributor must mount in the stock location and maintain the same firing order as a factory produced engine for the make and model engine being used. All engines must be assembled with Stock OEM type parts only. A 3/4inch plug must be installed in the oil pan for inspection; the access hole must be in line with a connecting rod journal. No roller-type cam bearings are allowed. Stock type magnetic steel connecting rods with stock length for engine being used, i.e.: 350 C.I. 5.70". Connecting rod beams may be cleaned and peened for strength. Only flat tappet, magnetic steel hydraulic or solid lifters are permitted. No roller tappets mushroom, or radius valve lifters allowed. Lifters must be original size and in stock location for engine block being used. Flat top stock with skirt or after-market equivalent, stock piston with stock pin location. Piston cannot come up higher than block deck surface. Minimum ring 1/16 1/16 3/16. No gas ports. Only flat tappet cam permitted. Roller rockers permitted. No stud girdles allowed. Must have stock stroke for engine being used. No internal or external polishing or lightening of block allowed. No internal painting. Maximum compression ratio not to exceed 10.5 to 1. Stock magnetic steel lifters only. It must contain snap ring. No mushroom or radius lifters are allowed. No rev kits allowed. Lifter bore to remain stock and in stock location for engine being used. Stock harmonic balancers only. Valve trains must be steel, No composite or titanium allowed. Oil pan sumps may be enlarged, must be stock appearing, straight sides must be maintained and must be steel. No dry sumps allowed. No belt or gear driven timing components are allowed. Cranks must weigh a minimum of 48 lbs. Inertia balancing is not allowed. Oil coolers are allowed. No lifter bore truing allowed.

### **CYLINDER HEADS:**

All cylinder heads must retain all factory dimensions and configurations as cast.

Valve size must be stock for heads being used, on all engines. 1.94 –1.5 or 2.02 –1.6 valves permitted. Vortec heads must use 1.94 –1.5 valve. No Bowtie Vortec heads.

Only one flat stock-type standard gasket may be used between the head and the intake manifold.

No wedge type gaskets or metal spacers are allowed.

Guide plates and screw in studs are permitted.

Heads may be machined for bigger valve spring and push rod clearance only.

Only steel valve springs and retainers are permitted.

No angle plug or bowtie heads are allowed.

Mandatory rocker arm ratio of 1:5 or 1:6 is permitted.

High Banks Speedway reserves the right to impound 1 head for inspection by outside independent sources. If legal, head will be available no later than the following Wednesday at 12:00 noon.



## *High Banks Speedway 2027*

No titanium or hollow stem valves are allowed. Undercut stem valves are allowed.

Absolutely no modifications/alterations allowed. This includes grinding, porting, polishing, etching, coating, painting, acid dipping, port matching or increasing entry port size. No, machine or hand work will be allowed above the valve in the “bowl area.”

The following aftermarket stock replacement unaltered cast iron cylinder heads will be approved for use in competition:

- E-Force P/N 175679 Casting 3 10024561
- World Parts P/N 43610
- Ford and Chrysler participants call for more information.

### **INTAKE MANIFOLD:**

The following after-market aluminum intake manifolds are permitted: Edelbrock Series Chev-#2101, Chevrolet with Vortec #2116, Chrysler #2176, Ford 2181, 2665, and 2750. Early design manifolds carrying the same part number will not be allowed.

2-bl or 4-bl cast iron manifold is permitted provided it is OEM for a production car. No marine applications.

Absolutely no modifications/alterations allowed. This includes grinding, porting, polishing, etching, coating, painting, acid dipping, port matching, increasing entry port size. No beveling, or machining of the carburetor mounting surface allowed.

Intake must be approved by High Banks Speedway officials.

Intake may be machined internally 2 inches from the top of the manifold.

### **CARBURETOR:**

Stock Holly #R4412 2-bl 500 cfm is the only legal Carburetor. Carburetor must meet Holley specifications.

No polishing, grinding, or drilling (i.e., Metering block) of holes allowed.

Choke, blade, and rod may be removed.

Size and shape of boosters must not be altered.

Booster height must remain stock.

Jets of any size may be used.

Venturi area must not be altered in any way.

Casting ring must remain completely visible and may not be removed.



## *High Banks Speedway 2027*

Base plates must not be altered in size or shape.

No holes may be drilled in the base plate.

Stock butterflies must not be thinned or tapered.

Screw ends may be cut even with the shaft, but screw heads must remain stock.

Throttle shafts must remain standard and must not be thinned, cut, or nicked in any matter.

Only a one-piece metal carburetor spacer, a maximum of 1 inch, may be installed between the intake manifold and the carburetor. Spacer may have no taper or bevels. No anti-reversion or similar machining allowed.

The maximum gasket thickness shall be .065.

No electric fuel pumps are allowed.

No cool air boxes allowed. No forced air devices. Air deflector must be attached to the body only.

The top and bottom of the air filter housing must be solid and must be the same diameter. A maximum of a one-inch lip will be permitted from the air filter element to the edge of the air filter housing top and bottom. No heat or air deflectors attached to the air cleaner are allowed.

\*\*\* Please refer to General Section for rules and regulations applicable to all divisions\*\*\*